OWNER'S MANUAL







To keep your bike in perfect running condition, please follow the periodic maintenance services which includes 3 Free and subsequent Paid services, as per the schedule contained in this booklet.

अधनी बाइक को सही धानती हालत में रखने के लिए, कृपया आवधिक रखरखात संवाजी का पासन करें जिसमें 3 नि:शुरूक और बाद में मुनतान संवापं शामिक हैं, इस परिलक्ष में दिए कर अनस्वी के प्रति।

आपजी बाहेक परिपूर्ण स्थितीत चाल् ठेवण्यासाठी कृत्वा या बुकलेटानाचे विलेल्पा रोइप्लानुसार पीरिऑडिक मेन्टेनन्स सर्विशेचे अनुकरण करा. पात 3 की आणि त्यानंतरच्या पेड सर्विशेस समाविष्ट आहेत.

ನಿಮ್ಮ ಬೈಕ್ ಸಂಪೂರ್ಣ ಚಾಲನಾ ಸ್ಥಿತಿಯಲ್ಲಿರಿಸಲು. ದಯವಿಲ್ಲು ಈ ಕೈಪಿಡಿಯಲ್ಲಿ ಸಮೂದಿಸಲಾದ ಕಮ್ಯೂಲ್ ಸಂತ ನಿಯತಕಾಲಿಕ ನಿರ್ವಹಣ ಸೇವೆಗಳನ್ನು ಅನುಸರಿಸಿ. ಇವು 3 ಉಚಿತ ಮತ್ತು ಸಂತರ ಪಾದತಿ ಸೇವೆಗಳನ್ನು ಒಳಗೊಂಡಿರುತ್ತದೆ.

உங்களுடைய எயக்கை லிக நன்றாக ஒடும் நிலையில் வைத்திருட்டிதற்கு. இந்துக் கையேட்டில் கொடுக்கட்டட்ட அட்டவணையில் உள்ளவறு 3, வசை மற்றும் தொடர்க்கியான கட்டன சேலையகளை உள்ளடக்கிய காலமுறை புராமரிப்பு சேலையை அப்பு செட்டிர பின்பற்றவும்.

మీ లైక్ చక్కటి రెన్నెంగ్ కండిషన్ లో ఉందాలంటే బుక్ లెల్లో ఉన్న పెడ్యూల్ ప్రకారం క్రమం తెబ్బకుండా మేయింటెసెస్స్ సర్వీకు చేయించింది, ఇందులో **8 ఉపిత సర్వేమారు,** ఆ **చ్యాక పెయిట్ సర్వేమిలు ఉన్నాయి.**

Doc. No. 71120169

നിങ്ങളുടെ ബൈക്ക് തികത്ത റണ്ണിംഗ് കണ്ടിക്തില്സംരക്ഷിക്കാന്3 സൗജന്വവും തുടര്ന്ന് പണം നല്കിയുള്ളതുമായ മെയ്ന്റാന്ന്ഡ് സബിസുകള്യെവായി സമയാരുത്തുതം ഈ ബുക്ലൂറ്റിലെ ക്രകപദ്ദികയില് കാണിചച്ചപുകാരം പാലിക്കുക

আগনার নাইক নির্ভুলকারে চালু অবস্থান রাখান জনা, নির্দিষ্ট সময় অবন লক্ষণানাক্ষণ পরিকোর অনুনান করুল বার মধ্যে আদে ১টি বিলামূল্য এবং পরবর্তী মূলাভিত্তিক পরিকার, এই পরিকার অবর্তনান ভালিকা জনানাধী।

අතුර වනය වූහාණ අද අපවාරණට වනය සඳහනමු | අතුරේ කර්ගෙන පෙරේ වෙතුරිණ කළේම පදුළ 3 දු පාසන ග වසරදා පෙර බහසෙන පෙරෙන් පෙරම දෙද, කරේමට පළදා පැතු ලලගෙන වෙළහෙන්න

તમારી આઇકને સંપૂર્ણ ચાલુ સ્થિતિમાં રાખવા માટે. કૃપા કરી નીચે મુજબ સમગ્રાંતરની જાળવણી સર્વિસનું પાછન કરો જેમાં **ર ચકૃત અને પછી પૃકવણી.** સર્વિ**લની સમાવેલ શાલ છ,** બા પુસ્તિકામાં સમાવિજ સમયકમ મુજબ

ਆਪਣੀ ਸਾਈਕ ਨੂੰ ਦਲਦੀ ਹਾਲਤ ਵਿੱਚ ਵਪਣ ਲਈ , ਕਿਰਪਾ ਆਵਰਤੀ-ਸੰਭਾਲ ਸੇਵਾ ਦਾ ਪਤਨ ਕਵੇਂ ਜਿਸ ਵਿੱਚ **ਡਿਪੂਸਰ ਕਈ ਬਾਰ ਵਿੱਚ ਤੁਵਤਾਰ ਨੌਵਾਂਦਾ ਵਾਪਤ ਵਨ,** ਇਸ ਕਿਤਾਬ ਵਿੱਚ ਦਿੱਤੇ ਕਦੋਂ ਅਨੁਸੂਚੀ ਦੋ ਪਤਿ

আপোনৰ বাইকখন সচিকভাৱে চলি থকা ছিচিত কথিবলৈ, অনুযাহ কৰি নিছমীয়া অঞ্যবদাৰ দেব অনুসৰণ কৰিব য'ত অনুষ্ঠিত থাকে 3 টা **চিনানুনীয়া আৰু ভাব নিছম কৰিবাৰ কৰা লেৱ**, এই পুৰিকাশনৰ অনুষ্ঠিত অনুষ্ঠি অনুসৰি।

اپنی باتیک کر بہترین رفنگ حالت میں رکھنے کے لیے، برانے مہرباتی وقت وقت سے - فیٹلینس کی خاصات پر حمل کریں جس میں شامل ہیں: اس کتابچہ میں نئے گئے وقت کے مطابق 3 ملت سروسز اور بعد کی پیڈ سروسز

REV. 01, DEC., 2021

Foreword



Welcome to the Pulsar family!

You are now the proud owner of the next generation **Pulsar NS 125** BS VI India's No.1 sports bike. By No.1 we are talking about unparalleled performance, superior technology and incredible market leadership that Pulsar today enjoys. This makes the Pulsar you ride, unbeatable and unchallenged both on and off the road.

Before you ride out, please read this Owner's Manual carefully and familiarize yourself with the operating mechanism, controls and maintenance requirements of your Pulsar. This will ensure you a safe and trouble free ownership experience.

To keep your bike in perfect running condition and deliver consistent performance, we have specially programmed the periodic maintenance services which includes 3 Free and subsequent Paid services, as per the schedule contained in this booklet. We earnestly advise you to avail all these services at any of our Bajaj Dealers or Authorised Service Dealers (ASD), who are well equipped with all necessary facilities / genuine parts / oil and trained manpower to ensure the best care for your Pulsar. Your **Pulsar NS 125** BS VI comes with a warranty of 5 Years or 75,000 Kms whichever occurs earlier from the date of sale. For details please refer to "Warranty: Scope & Limits" given in this manual.

Should you require any additional information feel free to contact us on helpline numbers or e-mail us at: customerservice@bajajauto.co.in or visit the Bajaj Auto website **www.bajajauto.com**

To be a part of the Pulsarmania, visit <u>www.mypulsar.com</u> and join the Pulsar fanpage on facebook: <u>www.facebook.com/mypulsar</u>

Rev up, shift gears and enjoy the Pulsar experience...

SERVICE DEPARTMENT BAJAJ AUTO LIMITED

TABLE OF CONTENTS



Description

1.	Technical Specifications	1
2.	Identification Data	3
3.	Location of Parts	4
4.	Fuel Tank Cap / Fuel Tap	5
5.	Matte Finish Painted Parts Cleaning / Steering cum Ignition Lock	6
6.	Speedometer Details	7
7.	Speedometer Setting	9
8.	Control Switches	11
9.	Rear seat / Tool kit	13
10.	Front Seat / Battery	14
11.	Fitment of Front & Rear Seat	15
12.	Daily Safety Checks	16
13.	How to ride your Bike	17
14.	Safe Riding Tips	22
15.	Engine Oil	23
16.	Tubeless Tyre	24
17.	Battery	25
18.	Periodic Maintenance Information	26
19.	Brake Fluid	28

20.	Free Service Guidelines	29
21.	Periodic Maintenance & Lubrication Chart	30
22.	Non Use Maintenance	38
23.	Warranty Scope & Limit	39
24.	Delivery Certificate	42
25.	Battery Warranty Card	43

Safety and Warning information:



Warning: This indicates that a potential hazard or injury to you or other persons & to the vehicle can happen if advice provided is not followed.



Caution: This indicates that a potential hazard that could result in vehicle damage. Follow the Advice provided with the caution.

Notice: The description and illustration in this booklet are not to be taken as binding on the manufacturers. The essential features of the type described and illustrated herein remaining unaltered. Bajaj Auto Limited reserves the right to carry out at any moment without being obliged to bring this booklet uptodate & to do modifications on the vehicle, parts or accessories as may be convenient and necessary.

TECHNICAL SPECIFICATIONS



Parameter	Specification
Engine	4 Stroke, Single Cylinder
Bore x Stroke	52 mm x 58.6 mm
Engine Displacement	124.45 cc
Compression Ratio	10+/- 0.5 : 1
Idling Speed	1300 +/- 100 RPM
Max. Net Power	12 PS at 8500 RPM
Max. Net Torque	11 Nm at 7000 RPM
Ignition System	DC
Spark Plug	2 Nos.
Spark Plug Gap	0.7 ~ 0.8 mm
Lubrication	Wet sump forced Lubrication
Transmission	5 speed constant mesh
Gear shifting Pattern	1 Down 4 Up
Engine Cooling	Air cooled
Starting Aid	Self & Kick
Combined Braking System	
Front Brake	Disc
Rear Brake	Drum

Parameter	Specification	
	Full 12 Liters	
Fuel Tank Capacity	Usable Reserve 2.6 Liters	
Dimensions		
Length	2012 mm	
Width	810 mm	
Height	1078 mm	
Wheel base	1352 mm	
Ground Clearance	178 mm	
Tyre Size Front	80/100-17 Tubeless	
Tyre Size Rear	100/90-17 Tubeless	
Tyre Pressure		
Front	1.75 Kgf/cm² (25 PSI)	
Rear (Solo)	2 Kgf/cm² (28 PSI)	
Rear (with pillion)	2.25 Kgf/cm² (32 PSI)	
Electrical System	12 Volts DC	
Battery	12V 4Ah VRLA	
Head Lamp	Bulb-35/35 W	

TECHNICAL SPECIFICATIONS



Parameter	Pulsar NS 125 BS VI
Position Lamp	Bulb-12V,3W-2 Nos.
Tail / Stop Lamp	LED
Side Indicator	Bulb 10W-4 Nos.
Neutral Indicator	LED-Green
Hi-Beam Indicator	LED-Blue.
Speedometer Illumination	LCD-Orange
Fuel Level Indicator	LCD Bar
Malfunction Indicator	LED-Yellow
Low Battery Indicator	LED-Red
Bajaj Logo	LED-Blue
REV Indicator	LED-Orange
Service Reminder	LCD
Side Stand Indicator	LCD
Rear No. Plate Lamp	Bulb 12V,3W
Horn	12V DC
Vehicle Kerb Weight	141 kg.
Vehicle Gross Weight	291 kg.

Note:

- All dimensions are under UNLADEN condition.
- Above information is subject to change without any notice.
- This vehicle complies to BS VI standard
- Automatic Headlight ON (AHO) is as per Government Regulation.

IDENTIFICATION DATA



The Frame and Engine serial numbers are used to register the motorcycle. They are the unique alpha-numeric codes to identify your particular vehicle from others of the same model and type.



Frame Number LocationOn RH Side of Steering Tube (Alpha-Numeric - 17 Digits)

Engine Number LocationOn LH Side Crankcase Near Gear
Change Lever (Alpha-Numeric - 11 Digits)



LOCATION OF PARTS





Fuel Tank Cap / Fuel Tap







- To open the fuel tank cap, open the flap. Insert the key in the lock and turn it clockwise and lift fuel tank cap.
- To lock the 'Fuel Tank Cap' insert the key in the lock and turn it clockwise and press fuel tank cap. 'Click' sound ensures cap is fully locked.

Precaution:

Don't attach metallic 'Key chain' as it may damage paint of petrol tank cover.

- Do not use adulterated fuel or fuel additives as it will result in Kerustian & Ingaing Official time of the cover.
- Do not REV UP engine RPM above 9500 in standstill condition.
- Never drive by disconnecting wheel speed sensor.



Fuel Tap

Fuel tap lever has following positions.

Д	ON : When fuel level is above reserve position.	
A	RES : When fuel level is below reserve position.	
	OFF: When fuel supply is to be cut off.	

Care to be taken for Fuel Tank & Steering cum Ignition Lock



Matte Finish Painted Parts Cleaning

- Use Colin or dish washing detergent solution for cleaning. (1 spoon in ½ bucket water)
 Remove foreign substances like insect remains, road debris using a soft brush.
- 2. Use microfiber cleaning cloths Ex.- Muslin cloth for painted parts cleaning.
- In case petrol is spilled out on white/light colour petrol tank, it is to be immediately cleaned with clean soft cotton cloth to prevent permanent stain marks on petrol tank.

Don'ts:

- Do not use any gloss enhancement products / wax / sprays for gloss enhancement.
- Do not use products that are even mildly abrasive, such as polishes, glazes, or rubbing compounds.
- Do not use mechanical cleaners/polishers.
- Do not use terrycloth or paper towels or shine enhancement products.
- Do not rub the finish vigorously, this will burnish the paint finish, causing a permanent shiny spot. Shiny spots cannot be removed.
- No Polishing/Teflon coating on painted parts.



Steering cum Ignition Lock:

It has three positions.

•	LOCK: Steering locked. Ignition OFF.
Ø	OFF: Steering unlock. Ignition OFF.
8	ON: Steering unlock. Ignition ON.

To Lock the Steering: To lock the steering, turn the handle bar to the left side. insert the key & Push, Turn the key to "LOCK" position and remove the key. **Steering locking on handle position left hand side only.**

To Unlock the Steering : To unlock steering, insert the key in steering cum ignition lock & turn it clockwise to "OFF" or "ON" position.

Key: A common key is used for 'Steering cum Ignition lock', 'Fuel tank cap' & 'Rear Seat'.

Speedometer Details





- 1. Fuel Level Indicator: It shows fuel level in fuel tank.
- **1A.** Low Fuel Indicator **□**: It blinks if fuel bar is ≤1.
- **2. Tachometer Dial:** It shows engine speed in RPM.
- Turn Signal Indicator (LH & RH): When Turn signal switch is turned to Left or Right, Turn pilot Indicator - LH or RH will flash.
- Neutral Indicator: It glows when transmission is in Neutral & Ignition switch 'ON' and kill switch in 'Engine ON' position.
- **5. Hi Beam Indicator:** When Headlight is 'ON' & Hi beam is selected with engine running, Hi beam indicator will glow.

- Low Battery Indicator: It indicates battery needs charging.
- **13.Malfunction Indicator** (\leftarrown: It indicates malfunction in sensors / actuators. It remains OFF while engine running.
- 8. Bajaj Logo: Bajaj logo flying 'B' continuously glow.
- Mode Button: Mode button used for changing the mode while selecting & setting Trip1, Trip2, ODO, Clock & Service reminder.
- 10. Set Button: It is used for setting Clock & Service reminder.

Speedometer Details





- **11. Engine Rev Indicator:** It blinks when engine RPM is between 9500 to 10000 RPM. Continously ON at RPM more than 10000.
- 12.Service Reminder (, 'Wrench' symbol glows when ODO meter reading reaches to set Kms. for service. This Icon will flash at -

1st: 450 km 2nd: 4950 Km 3rd: 9950 Km 4th: 14950 Km

and subsequently at each 5000 kms. Icon will continue to glow till it is reset. This icon is to be reset after service is carried out.

13. Side Stand Indicator: It glows when Side stand is down & ignition switch is 'ON' and kill switch in 'Engine ON' position.

Side stand down condition is interlocked as given below.

Condition	Result
Vehicle in 'N'	Self start / kick start possible but as soon as vehicle is put in gear, engine will get cut off.
Vehicle in Gear	Engine will not start by self / kick.

- 14. Digital Clock: It indicates time in HR : MM (AM/PM)
- **15. Speedometer:** Vehicle speed will be displayed in digital form in Km / h.
- **16. Odometer:** The odometer shows total distance the vehicle has covered. Odometer can not be reset to 'Zero'.
- **17.Trip Meter:** Trip 1 & Trip 2 shows the distance traveled since it was last reset to zero.

Speedometer Setting





1. Trip Meter Reset:

 Mode & Set push button is provided for selecting & resetting 'ODO/TRIP1/TRIP2'. LHS part of speedo console.

1.	Press mode push button for less than 2 sec.	Mode changes from 'ODO/TRIP1/TRIP2'
2.	Press set push button for more than 5 sec.	Selected mode 'TRIP1/TRIP2' will reset. Other TRIP mode will continue updating.

2. Service Reminder Reset ():

'Wrench' symbol glows when ODO meter reading reached to set Kms.

This icon will glow at-

1st: 450 Kms 2nd: 4950 Kms 3rd: 9950 Kms 4th: 14950 Kms & subsequently at each 5000 Kms.

Note: Bring the motorcycle at authorised BAL dealership for resetting the service reminder icon.

Speedometer Setting






3. Clock Reset:

- Digital clock indicates time in HR & MM separated by colon "."
- It is 12 hour clock.
- Initially ':' will be blinking
- Clock setting is possible in TRIP 1 mode only.

1.	Press mode push button for less than 2 sec.	TRIP1 Mode selected
2.	Press mode & set push button together for more than 2 sec.	" stops blinking Digits starts blinking
3.	Press mode button for less than 1 sec.	Hour digits will increases by one.
4.	Press set button for less than 1 sec.	Minutes digits will increases. If mode/set button is pressed continuously then digits will stop blinking.
5.	Press mode & set button together for more than 2 sec.	Set value will be saved Exit clock setting mode Digits stop blinking " start blinking
6.	Clock set mode is selected & no editing is carried out for more than 5 sec.	Auto exit without saving set value. If engine/vehicle rpm is given then system will exit from clock set mode without saving set value.

Control Switches





Left Handle Bar Switches


A. Hi / Lo Beam Switch : Head lamp low or high beam can selected.

: High Beam : L

: Low beam

B. Turn Signal Switch : When the turn signal knob is pushed to Left ($\langle \! \! \ \rangle \!\! \!$) or Right ($r \!\!\! \ \rangle \!\!\!\!$) respective indicator will start blinking.

To stop blinking push the knob in & release.



C. Horn Button: () Press button for sounding horn.

D. Pass Switch : Press the switch to operate high beam filament in head light. It is used to give signal to vehicles coming from opposite side while overtaking.

Control Switches





E. Starter Button:

Starter button operates the electric starter. It is recommended to start the engine with the transmission in neutral.

Vehicle in Gear - Press clutch lever & operate starter button to start the engine.

F. Engine Kill Switch:

The engine kill switch is used for switching $\ensuremath{\mathsf{ON}}$ & $\ensuremath{\mathsf{OFF}}$ the engine.

: Engine OFF : Engine ON **AHO Feature** (Automatic Headlight 'ON')
There is no 'Light switch' on RH control switch.

Ignition switch 'ON' & Engine Running

Speedometer lamp, Tail lamp, Number Plate Lamp, Pilot Lamp & Control Switches Illumination will get 'ON' in addition to above, headlamp will get ON as given below.

Hi/Low beam Switch	Headlamp Status	Effect of Pass Switch
Low beam ⑤	Low beam 'ON'	Hi beam 'ON'
Hi beam ≣O	Hi beam 'ON'	No change

 Headlamp will be turned ON only at Engine running condition.

Rear Seat / Tool Kit







- Insert Key into lock (A)
- · Turn the key clock wise.
- Pull upward front end of 'Rear seat'
- Take out 'Rear seat'





Tool Kit Location

- · It is located below the 'Rear seat'.
- · 2 rubber straps are provided to hold the tool kit.




CAUTION: Always fit rubber strap for locking tool kit.

First Aid Kit Location

• It is kept inside seat cowl RH side.

Front Seat / Battery







Removal of Front Seat


- · First remove 'Rear seat'.
- Remove 'Front seat' mounting bolts (B).
- Pull backward rear end of 'Front seat'.
- · Take out 'Front seat'.


Battery


• It is located below 'Front seat'.

Fitment of Front & Rear Seat









Fitment of 'Front Seat'

- Match the lugs of 'Front seat' (A) with chassis bracket (B).
- Push 'Front seat' toward petrol tank.
- Match 'Front seat' rear brackets (C) with the holes provided on chassis.
- · Tighten the bolts (D).

Fitment of 'Rear Seat'

- First make sure 'Front seat' is fitted properly.
- · Place 'Rear seat' on fitment location.
- · Insert bracket (E) of seat into hook (F).
- Match the rod of 'Front seat' (G) with seat lock (H).
- Press front portion of seat.

Daily Safety Checks



Before riding motorcycle be sure to check following items. Please give proper importance to these checks and perform all of them before riding motorcycle.

If any irregularities are found during these checks, refer to the Maintenance chapter & see your dealer for the action required to return the motorcycle to a safe operating condition.



Warning: Failure to perform these checks every day before you ride may result in serious damage or severe accident.

- Enough **fuel level** for planned distance of journey. No fuel leakage in fuel lines.
- Engine oil level (between upper and lower level mark)
- Front brake lever free play Not applicable for disc brake vehicles.
- Throttle cable play of 2 ~ 3 mm. Smooth operation and positive return to closed position,
- Brake Fluid level above MIN mark provided on Front reservoir.

- Drive Chain slack of 20 ~ 30 mm adequately lubricated.
- · Function of all lights & horn
- Clutch lever play 2 to 3 mm
- Rear Brake pedal free play 10 \sim 20 mm
- Smooth **steering movement** without restriction
- Main Stand / Side stand return to their fully up position.
- Correct **inflation pressure** in both tyres Adequate tyre tread depth no cracks / cuts.
- · Correct rear viewing span adjustment of mirror.
- Cleaning cloth not to be kept in vicinity of high temperature zone e.g. engine, silencer assy, starter motor etc.



1. Starting The Engine:

- Turn ignition switch key to 'Q' position.
- Put Keep kill switch in '\(\O\)' position.
- Confirm that transmission is in neutral / press the clutch lever.
- · Keep throttle completely closed, operate self start button or apply kick to start the engine.
- Release kick as soon as engine starts.

Note: Before starting the engine, in ignition key off condition, press the clutch lever & operate kick lever all the way down for 5-6 times. Then release the clutch lever.

Auto choke

BS VI Carburettor

This practice ensures lubrication of clutch components for their longer life.

This vehicle is equipped with BS VI carburettor having Auto choke.

The control unit operates ON / OFF function of Auto Choke. No manual operation is required.

Auto choke ensures smooth starting of engine in all weather conditions.

Note: Do not touch / distrub setting of idling & air screw provided on BS VI carburettor. For any performance related issue, take the vehicle to BAL authorised workshop.



Note:

The motorcycle is equipped with a Clutch switch. This switch facilitates engine starting in neutral and gear position.


Gear Position	Clutch lever position
Neutral	Released
Gear	Fully pressed

Do not let the engine idle longer than 3 minuets otherwise it will overheat.

 Incase of battery discharged condition please bring the vehicle to bajaj authorised workshop for repairs.

2. Shifting Gears:

- · Close throttle & depress the clutch.
- · Shift into next higher or lower gear.
- Open the throttle and release the clutch lever slowly and simultaneously.



3. Moving Off:

- Check that side stand is up.
- · Depress the clutch lever.
- Shift into 1st gear.
- Open the throttle and release the clutch lever slowly and simultaneously.
- As the clutch starts to engage, open the throttle a little more, giving the engine just enough rpm to keep it from stalling.



Recommended Speed for Shifting Down

 * 	
From 5 th to 4 th Gear	45 km/h
From 4 th to 3 rd Gear	35 km/h
From 3 rd to 2 nd Gear	25 km/h
From 2 nd to 1 st Gear	15 km/h



Warning: When shifting down to lower gear, do not shift at such high speed that engine rpm jumps excessively. This may cause engine damage, & rear wheel may skid. Downshifting should be done at recommended speeds as shown in table above.

4. Braking:

- Close the throttle completely, leaving the clutch engaged (except where shifting gears) so that the engine braking will help slow down the motorcycle.
- Shift down one gear at a time so that you are in Neutral when you come to a complete stop.
- When stopping, always apply both brakes at the same time. De-clutch as necessary to avoid engine stalling.
- Never lock the brakes, or it will cause the tyres to skid.
 When cornering, use brakes judiciously and do not declutch. Reduce your speed before you get into the corner.
 For emergency braking, disregard downshifting, and concentrate on applying brakes as hard as possible without skidding.



5. Stopping the Vehicle:

- Close the throttle completely.
- Shift the transmission into neutral.
- Bring the vehicle to complete stop.
- Turn the ignition switch off.

6. Parking the Vehicle:

- Support the motorcycle on a firm level surface with the side stand / main Stand
- · Lock the steering.



CAUTION: Do not park on a soft or steeply inclined surface or the motorcycle may fall over.

Whenever vehicle is fallen, remove plug of 'Y connecter drain tube' & drain out accumulated petrol.



Location : Near Kick Lever

'Y' Connector drain tube plug

7. Running IN

Proper running-in is important for the better life & trouble free performance of the vehicle.

• During first 2000 kms running-in period do not exceed following speed limits.

Kms	1st	2nd	3rd	4th	5th
0 - 1000	10	20	30	35	45
1000 - 2000	15	30	40	45	55

- Always keep the speed below the limits mentioned in the table.
- Do not race the engine excessively.
- Do not start moving or race the engine immediately after starting. Run the engine for a minute at idle speed to give the oil a chance to workup into the engine.

Fuel Saving Tips:

A well maintained vehicle and good driving can contribute a lot to the saving of petrol. Following are a few simple fuel saving tips.



Fuel Saving Tips :

A well maintained vehicle and good driving can contribute a lot to the saving of petrol. Following are a few simple fuel saving tips.

- Ride smoothly and steadily at an optimum driving speed to get best mileage.
- · Avoid harsh braking.
- Change the gear judiciously according to the speed and load requirement.
- · Don't overload the vehicle above the specified payload.
- · Use the accelerator judiciously.
- Cut off the engine if you want to stop for more than two minutes.

How to check mileage (Fuel efficiency)

Best way to calculate mileage is by following the full tank to full tank method.

- Fill way tank full up to small mouth (brim).
- · Run the bike for say 100 km.
- Fill the tank full again in same fuel filling station, probably with same fuel dispenser.
- · Divide kilometer run / fuel quantity filled.

Ensure following maintenance points to get optimum performance from your bike.

Fuel	Check fuel lines & connections for leakage.
Spark Plugs	Inspect and clean spark plugs. Adjust electrode gap. Replace spark plugs as per P.M. Chart.
Air Filter	Clean the air filter element periodically. Replace as per Periodic Maintenance Chart.
Engine Oil	Check engine oil level. Always use recommended grade and quantity.
Brakes	Ensure that the brakes are not dragging / binding.
Clutch	Ensure correct clutch lever play.
Tyre Air pressure	Always maintain recommended tyre pressure.
Brake Fluid	Always maintain brake fluid level above minimum mark. Ensure no leakage of brake fluid in brake system.

Safe Riding Tips



- Always wear Helmet while driving or riding. Your helmet should conform to Indian standards.
- Read thoroughly the instructions given in this manual and follow them carefully.
- Avoid unnecessary accessories for the safety of both rider and other motorists.
- Get familiar and follow traffic rules & regulations in your states as well as general traffic signs.
- Familiarise yourself well with starting, acceleration and braking of the vehicle.
- When applying the brakes, use both front & rear brakes simultaneously. Applying only one brake may cause the vehicle to loose control.
- Riding at proper speed, avoiding unnecessary acceleration and braking are important safety, fuel consumption and longer life of the vehicle.
- During monsoon, drive vehicle more cautiously. Remember vehicle skid more easily during light showers.
- Keep both hands firmly on handle bar & both feet securely on rider footrest. Do not take away both hands & / or feet from resting area as this is very unsafe.
- Do not use mobile phones while riding as it could lead to fatal accident.

- It is suggested to customer to take appropriate care in area of heavy monsoon or high rainfall area. The appropriate surface preventive coat to avoid rusting / poor surface finish on account of adverse atmospheric conditions.
- Always carry vehicle registration & insurance papers, and a valid driving licence with you.

General Maintenance Tips :

- Vehicle cleaning to be done with soft & clean wet cloth to avoid scratches on painted parts.
- Clean & lubricate all the important parts as detailed in a periodic maintenance chart.
- Do not apply direct water jet on painted, electrical / electronic parts.
- Do not obstruct engine cooling by adding mud protection sheet from front
- Drive cautiously. Start early & reach your destination safely.
- Avoid driving on loose sand or stones where vehicle is likely to skid.
- Properly wrap-up loose clothes while driving or riding to avoid entangling in wheel or other objects on road.
- · Always concentrate on riding for safety.

Engine Oil







A : Oil Filler Cap

B : Oil Level Gauge

C : Upper Level

D : Lower (Min) Level

Engine Oil Level Checking:

- Check engine oil level every day. Park vehicle on center stand.
- Check oil level through oil level gauge 'B'.
- Always maintain engine oil level between upper (C) and lower (D) mark provided on Cover RH. Top up with specified grade of oil if the oil level is below lower level mark.

Engine Oil Capacity:

Refill at servicing: 1000 ml

During engine overhaul: 1100 ml

Recommended Engine Oil:

Always insist on Bajaj Genuine Engine Oil for optimum engine performance and warranty benefits. It is a specially formulated oil for vehicles with DTS-i engines.

Model	Recommended Engine oil	Grade
Pulsar	Bajaj DTS-i 10000	SAE 20W50
NS 125	BS6 Compliant	JASO 'MA2' API SN

- For all BS6 Vehicles, above BS6 compliant engine oil is to be used only. Use of BS6 engine oil will give prolonged life of catalytic convertor.
- \bullet Engine oil replacement frequency : 1^{st} service & then every 10,000 Km.
- Engine oil level top-up frequency : Every 5000 km.



CAUTION:

- It is most important to adhere to recommended grade & frequency of oil change for the purpose of long life of critical engine components. For details refer periodic maintenance chart.
- · Do not reuse drained oil.

Tubeless Tyre



Tubeless Tyre:

- In this motorcycle tubeless tyres are fitted.
- Tyre seating edge area of wheel rim should not get damaged while removing / fitment of tyre.
 Inadequate sealing will lead to air leakage.

Wheel Puncture:

- Visit nearest known tubeless tyre repair shop to remove puncture.
- Remove puncture by Filler or Plug method only.
- Do not use patch method to remove puncture of tubeless tyre.

Tyre Pressure:

Keep appropriate tyre pressure as mentioned below to increase life of the tyre & for better fuel consumption.

Front : 1.75 kgf/cm² (25 PSI)

Rear (Solo) : 2 kgf/cm² (28 PSI)

Rear (with pillion) : 2.25 kgf/cm² (32 PSI)

- Tyre warranty is settled by tyre manufacturer.
- Decision is taken based on tyre wear and running of vehicle.
- BAL settles tyre warranty for only imported tyres.

Note : Incase the motorcycle is fitted with imported tyres. compliance to respective indian standard & central motor vehicle rules has been ensured.

Battery





Battery: 12V - 4Ah VRLA

· Battery is located below front seat.

Battery Features:

- · No topping-up is required
- · Reduced self discharge, Enhance safety.
- No vent tube open to atmosphere hence no discharge of electrolyte through vent tube.
- Battery make may differ from vehicle to vehicle.



CAUTION: Do not drive / run vehicle in battery disconnected condition. It may lead to damage of electrical / electronic components.

- Environment care must be taken to dispose off the used battery.
- It is always recommended to hand over the same to the Authorised battery / Bajaj dealer for proper disposal of the same.
- When low battery icon pop-up on speedometer display, it is advised to reach Bajaj dealer & get it charged immediately.
- Warranty on battery is 18 months from the date of purchase of vehicle.

How to keep battery healthy?

- · Switch 'Off' ignition when engine is not running.
- Get battery checked/ charged during periodic services.
- Do not add extra electrical accessories such as -Remote, Bigger Horn, Musical brake light etc. This will reduce life of battery
- Disconnect battery +ve & -ve wires if vehicle is to be stored for more than 2 weeks. This avoids self discharge.

Periodic Maintenance Information

pulsar

Spark Plug

· Remove spark plugs by using plug spanner.

· Clean the spark plugs.

 Adjust the gaps if incorrect by bending outer electrode carefully.

Spark Plug Gap : 0.7 to 0.8 mm.

Spark Plug : 2 Nos.





Drive Chain Slackness

- Chain slackness will have to be adjusted whenever required.
- Std. Chain slackness 20 ~ 30 mm.
- Marking on chain adjusters should be identically positioned on both sides.







Periodic Maintenance Information





Drive Chain Cleaning

Drive chain must be cleaned & lubricated as per periodic maintenance schedule.

Drive Chain (O-ring type)

- 'O' rings must always be kept wet for best performance hence lubricate every 500 Km.
- O-ring chain lubrication can easily be done by owners using Bajaj 'Chain Lube Spray Can' available with Bajaj dealers.



Drive Chain Lubrication

Method of O-ring Chain Lubrication:

- Park vehicle on center stand.
 Clean the chain by using lint free cloth (If excessive mud / slush found approach Bajaj Service Center for proper cleaning)
- Shake the can vigorously by holding vertically upright till the noise of steel ball inside heard uniformly.
- Hold spray can at the back of rear sprocket with extension tube nose at 5~10 cm.
- Rotate the wheel in reverse direction & spray the tube on middle portion of the chain up to full length of the chain.





Front Brake Fluid Reservior

Front Brake Fluid Level

- Front brake fluid reservoir is located on RH side of Handle bar.
- To check the brake fluid level, Park the vehicle on center stand with handle bar in straight ahead condition.
- Always ensure that brake fluid level is above 'MIN' mark given on inspection Window.



 Incase of level drop, use only DOT-4 brake fluid (from sealed container) for top up & replacement.

Free Service Guidelines



Instruction to avail Free Service through Digitized Free Service Coupon

Please follow following procedure: -

- Please provide your mobile number to Dealer at the time of buying of new Bajaj Vehicle.
- In case of change in mobile number, please update to Dealer / ASD.
- When you are at Dealership / ASD workshop for availing Free Service, you will receive the 'Unique Coupon Number' (UCN) through SMS in your mobile.
- Please inform the UCN to Dealer / ASD at the time of Free Service.
 (ASD-Authorised Service Dealer)

Periodic Service Criteria									
Service	Kms								
1st Free Service	30~45	500~750							
2nd Free Service	240	4500~5000	earlier						
3rd Free Service	360	9500~10000	curs ea						
Subsequent Paid services	120 Days from last Service	Every 5000 Km after previous service	whichever occurs						

Availing all Free / Paid Services, replacing mandatory periodic parts & engine oil will entitle warranty eligibility.

Periodic Maintenance & Lubrication Chart



		Recommended frequency - Service interval & Kms								
Sr.	Activities / Check	Servicing	1st (Free)	2nd (Free)	3rd (Free)	4th	5th	6th	7th	
No.	points	KMS	500 750	4500 5000	9500 10000	14500 15000	19500 20000	24500 25000	29500 30000	
1.	Servicing with water wash	1	1	1	1	1	1	1	1	
2.	Engine oil (Bajaj DTSI 10000 oil)	Top-up,R	R	Top-up	R	Top-up	R	Top-up	R	
3.	Engine oil Filter	R	R		R		R		R	
4.	Oil strainer	CL	CL		CL		CL		CL	
5.	Air cleaner element** & air filter cover 'O' ring. Drain tube cleaning.	R					R			
6.	Spark plug clean & check gap	CL,A, R			CL,A		CL,A			
7.	Valve tappet clearance	C, A				C, A			C, A	
8.	Carburetor rubber duct for hard resulting in loose fitment.	C,R				C,R	C,R	C,R	C,R	
9.	Engine breather tube for cracks.	C,R			C,R	C,R	C,R	C,R	C,R	
10.	EVAP system Hoses- check for cracks	C,R		C,R	C,R	C,R	C,R	C,R	C,R	

Periodic Maintenance & Lubrication Chart



	•								
· R	ecomn	nended	freque	ncy - S	Service	interva	ıl & Km	s	
8th	9th	10th	11th	12th	13th	14th	15th	16th	Remarks
34500 35000	39500 40000	44500 45000	49500 50000	54500 55000	59500 60000	64500 65000	69500 70000	74500 75000	
1	1	✓	1	✓	1	1	1	1	Ensure to prevent water entry in Petrol tank, Silencer & electrical parts. Use caustic free detergent for washing.
Top-up	R	Top-up	R	Top-up	R	Top-up	R	Top-up	Use BGO 20W50 BS6 Compliant Oil level window cleaning at every 10000 kms by petrol spray & nylon brush.
	R		R		R		R		Replace oil filter in 1st service & at every 10000 Kms.
	CL		CL		CL		CL		Oil strainer cleaning at the time of oil change.
	R				R				Replace viscous filter at every 20,000 kms
	CL,A		CL,A		R		CL,A		Replace at every 30000 Kms.
		C, A			C, A			C, A	
C,R	Replace if required								
C,R	Replace if required								
C,R	Drain EVAP "Y" connection drain tube.Replace if found cut / damaged								

Periodic Maintenance & Lubrication Chart



		Recommended frequency - Service interval & Kms								
Sr.	Activities / Check	Servicing	1st (Free)	2nd (Free)	3rd (Free)	4th	5th	6th	7th	
No.	points	KMS	500 750	4500 5000	9500 10000	14500 15000	19500 20000	24500 25000	29500 30000	
11.	Silencer drain hole cleaning	CL			CL	CL	CL	CL	CL	
12.	Wiring harness connections, routine & Conduit / PVC sleeve inspection.	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	
13.	Battery, connections & health by load tester. +ve terminal cap fitment.	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	
14.	Ignition switch contacts cleaning	CL,L			CL,L	CL,L	CL,L	CL,L	CL,L	
15.	HT coil connections (Primary and Secondary)	C,T		C,T	C,T	C,T	C,T	C,T	C,T	
16.	Starter motor & starter relay connections	C,T		C,T	C,T	C,T	C,T	C,T	C,T	
17.	Check fault code, Clear fault history, Update latest hex file if applicable	С	С	С	С	С	С	С	С	
18.	sealed Drive chain wear**- Clean, Lubricate & adjust. Replace if required	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	
19.	Main stand & side stand both pivot pin	C,L					C,L			





	Recommended frequency - Service interval & Kms												
R	ecomm	nended	freque	ncy - S	Service								
8th	9th	10th	11th	12th	13th	14th	15th	16th	Remarks				
34500 35000	39500 40000	44500 45000	49500 50000	54500 55000	59500 60000	64500 65000	69500 70000	74500 75000					
CL	CL	CL	CL	CL	CL	CL	CL	CL					
C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	C,A,T	Damaged conduit / PVC sleeves protection by applying electrical tape film				
C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	C,A,L,T	Apply petroleum jelly on battery terminals. Use midtronics battery tester				
CL,L	CL,L	CL,L	CL,L	CL,L	CL,L	CL,L	CL,L	CL,L	Use recommended WD40 spray				
C,T	C,T	C,T	C,T	C,T	C,T	C,T	C,T	C,T					
C,T	C,T	C,T	C,T	C,T	C,T	C,T	C,T	C,T					
С	С	С	С	С	С	С	С	С					
CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	CL,L,A	During 1st free service use OKS spray for chain cleaning without removing chain from vehicle. During other services clean chain with Diesel+SAE 90 oil ration of 50:50 & lubricate by SAE 90 oil.(Customer to use OKS chain lub spray at every 500 kms)				
	C,L				C,L				Use recommended AP grease.				



		Reco	mmenc	led fred	quency	- Servi	ice inte	rval & l	Kms	
Sr.	Activities / Check	Servicing	1st (Free)	2nd (Free)	3rd (Free)	4th	5th	6th	7th	
No.	points	кмѕ	500 750	4500 5000	9500 10000	14500 15000	19500 20000	24500 25000	29500 30000	
20.	Steering play	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A	
21.	Steering stem bearing & Cap steering bearing (Plastic)**	C,CL,L			C,CL,L		C,CL,L		C,CL,L	
22.	Front fork oil & seal	C,R	C,R	C,R	C,R	C,R	C,R	C,R	R	
23.	Rear Brake Shoes	C,R	C,R	C,R	C,R	R	C,R	C,R	R	
24.	Rear Brake Cam	CL,L		CL,L	CL,L	CL,L	CL,L	CL,L	CL,L	
25.	Swing arm NRB for more play	L								
26.	Front Brake pads for wear limit.	C,R	C,R	C,R	C,R	R	C,R	C,R	R	
27.	Check source of leakages if any in the brake system. Check Front brake hose condition. Check Brake fluid level and top up, if needed.	C,A,R	C,A,R	C,A,R	C,A,R	C,A,R	C,A,R	C,A,R	R	
28.	Rear sprocket fasteners for looseness.	C,T	C,T		C,T		C,T		C,T	
29.	Rear wheel rubber shock dampers for excess play.	C,R			C,R		C,R		C,R	
30.	Fairing & windshield well nuts for rubber cracks.	C,R			C,R	C,R	C,R	C,R	C,R	
31.	Clutch & Throttle cables free play adjustment	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A	
32.	Rear Brake Pedal	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A	
33.	Head light focus adjustment	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A	
34.	Check & confirm all bulbs / switches working.	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A	



* , · R	ecomm	nended	freque	ncy - S	Service				
8th	9th	10th	11th	12th	13th	14th	15th	16th	Remarks
34500 35000	39500 40000	44500 45000	49500 50000	54500 55000	59500 60000	64500 65000	69500 70000	74500 75000	
C,A									
	C,CL,L		C,CL,L		C,CL,L		C,CL,L		Replace if required. Use Limaplex grease for lubrication
C,R	C,R	C,R	C,R	C,R	R	C,R	C,R	C,R	Replace fork oil, oil seal and dust seal in pair at every 30000kms
C,R	C,R	R	C,R	C,R	R	C,R	C,R	R	
CL,L	Use AP grease.								
	L								Lubricate at every 40,000 kms
C,R	C,R	R	C,R	C,R	R	C,R	C,R	R	Replace at every 15000 Kms
C,A,R	C,A,R	C,A,R	C,A,R	C,A,R	R	C,A,R	C,A,R	C,A,R	Check & Top up DOT 4 brake oil in every service.Replace DOT 4 brake oil & Master / Caliper seals at every 30000kms
	C,T		C,T		C,T		C,T		Use model wise torque values.
	C,R		C,R		C,R		C,R		Replace rear wheel rubber shock damper if required
C,R	Replace if required.								
C,A	Replace cables if operation found hard.								
C,A									
C,A	Contact type switches if found sticky then use recommended WD40 spray								



		Recommended frequency - Service interval & Kms										
Sr.	Activities / Check	Servicing	1st (Free)	2nd (Free)	3rd (Free)	4th	5th	6th	7th			
No.	points	кмѕ	500 750	4500 5000	9500 10000	14500 15000	19500 20000	24500 25000	29500 30000			
35.	General lubrication – Clutch lever	L	L	L	L	L	L	L	L			
36	Tyre air pressure.	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A			
37.	Mirror position & joint firmness.	C,A	C,A	C,A	C,A	C,A	C,A	C,A	C,A			
38.	All fasteners tightness, few are, 1. Front & rear axle, 2. Swing arm axle, 3. Engine foundation, 4. Rider foot rest, 5. Pillion stay	С,Т	С,Т	С,Т	С,Т	С,Т	С,Т	С,Т	С,Т			

C: Check, A: Adjust, CL: Clean, R: Replace, T: Tighten, L: Lubricate

Note : Periodic parts, Oil, Coolant, Filters, All types of greases, Cleaning agents, Cables, Wear & tear parts, Rubber 'O' rings / oil seals / pipes, Gaskets to be replaced as per Periodic Maintenance and Lubrication Chart are mandatory and the same are chargeable to customer.

^{**}More frequent cleaning may be required while driving in dusty environment.



	* , * , '	•								
Recommended frequency - Service interval & Kms										
8t	:h	9th	10th	11th	12th	13th	14th	15th	16th	Remarks
-	500	39500 40000	44500 45000	49500 50000	54500 55000	59500 60000	64500 65000	69500 70000	74500 75000	
ı	-	L	L	L	L	L	L	L	L	Use recommended AP grease.
С	,А	C,A	Ensure model wise tyre air pressure.							
С	,А	C,A								
С	,Т	C,T	С,Т	C,T	C,T	C,T	C,T	C,T	С,Т	Use model wise torque values.

Non-Use Maintenance



Non-use maintenance is necessary if a vehicle remains off road for a longer duration (more than 15 days**). The correct and careful non-use maintenance carried out before storing the vehicle will prevent the vehicle from rusting and from such other non-operational damages like fire hazards.

- · Clean the entire vehicle thoroughly.
- Empty the fuel from the fuel tank.

 (If fuel' is left in for a longer time, the fuel will break and gummy substance could clog the carburettor).
- Remove spark plug & put several drops of engine oil into the cylinder. Kick engine over slowly a few times to coat cylinder wall with oil & install back spark plug.
- Set the vehicle on a box or a stand so that both wheels are raised off the ground.
- Spray oil on all unpainted metal surfaces to prevent rusting.
 Avoid getting oil on rubber parts or brake liners.
- Cover entire vehicle neatly. Make sure that storage area is well ventilated & free from any source of flames or spark.
- Fill 10% excess air pressure in both wheels.
- Do not apply oil on front brake disc / rear brake disc, to prevent rusting. If the front brake disc / rear brake disc rusts during storage, do not attempt to clean it with soap water. The rust will go off automatically during first few application of brake.

** For Battery:

- a. Remove battery and keep it on wooden plank, in properly ventilated area.
- b. Before taking the vehicle for use.
- Get the battery recharged from the Authorised Service Center / Battery Dealer.
- · Apply petroleum jelly on battery terminals.

Preparation for regular use after storage:

· Follow daily safety checks.

Warranty : Scope & Limit



Bajaj Auto Limited provides the following warranty in respect of the "Pulsar NS 125 BS VI" motorcycle manufactured by us.

Every possible care and precaution has been taken to ensure quality in respect of the material & workmanship in the vehicles manufactured by us. Bajaj Auto Limited will repair or replace at their Authorised Workshops, free of charge, part or parts there of as may be found, on examination, to have manufacturing defect within a period of 5 Years or 75,000 Kms., whichever is earlier from the date of sale subject to fulfillment of conditions stipulated in part A, B & C given here under

Note: Warranty is applicable for only first owner of vehicle.

Part A:

Warranty claims in respect of such items like shock absorbers, speedometers etc. though claimed through us, are subject to acceptance of the respective manufacturers. In all such cases the decision of the respective manufacturer will be final and binding.

Proprietory parts like tyres, tubes, battery are warranted by their respective manufacturers and should be claimed on them directly by the customer. Bajaj Auto Limited shall not be Liable to replace them though their dealer, however Bajaj Dealers will provide full assistance in referring such claims with respective manufacturer.

Bajaj Auto Limited undertake no liability in the matter of consequential loss or damage caused due to the failure of the parts. Delay, if any, at the repairing workshop in carrying out repair to vehicle shall not be a ground for extending the warranty period, nor shall it give any right to the customer for claiming any compensation for damages.

Bajaj Auto Limited reserves the right either to repair or replace the defective parts.

Where a defective part can be replaced by part/s of alternative brand/s, which are normally used by Bajaj Auto Limited in the course of manufacture, Bajaj Auto Limited reserves the right to carry out the replacement by a part or parts of any such alternative brand/s.

This warranty and any claim arising there, is subject to Pune jurisdiction only.

Part B:

No claim for exchange or repair can be considered unless the customer:

 Ensures that immediately upon detection of the defect, he approaches any nearest Authorised Bajaj Vehicle Dealers & Recommended Authorised Service Dealers with the concerned vehicle and enables him

Warranty: Scope & Limit



- to remove and despatch the part / parts attributing to the manufacturing defect to the Company.
- b. Produces the Owner's Manual, in original, to enable that dealer to verify the details.

It must be expressly understood that claims forwarded directly to us by the owner / customer will not be entertained at all and such defective part/parts thus forwarded by them will lie at our factory at their own risk, and this warranty shall not be enforceable.

To avail benefits of warranty, following are mandatory

- 1. Availing of Initial 3 Free Services without lapse.
- Availing paid services at subsequent 5000 kms. or 120 days from last service whichever is earlier without any lapse.
- 3. Availing of all services at the Authorised Vehicle Dealers & Recommended Authorised Service Dealers.
- Usage of only recommended engine oil
 "Bajaj DTS-i 10000" at specified frequency for drain interval of 10,000 kms. & engine oil level top-up at 5000 kms.
- Replacing mandatory periodic parts such as air filter, oil filter etc. as per periodic maintenance schedule.

Part C:

Further this warranty is NOT applicable to :

- Normal maintenance operations like brake & clutch adjustments, cleaning of fuel system, engine tune-up or such other adjustments.
- 2. Parts subjected to normal wear & tear like Clutch Plates, Brake Shoes, Chain, Sprockets, Fork Oil Seal, Spark Plug, Control Cables, Brake Pads.
- 3. Replacement of bulbs & rubber components like grommets, 'O' rings, bellows as well as filters, packings, gaskets, fasteners etc.
- 4. Painted parts. Only blistering or peeling off of paint film are covered under warranty. Any defect arising out due to external damages or due to usage of protective covers /additional protective coatings adverse atmospheric conditions etc. are not allowed like under warranty.
- 5. All consumables like Engine oil, Fork oil, Brake Oil, Grease etc. are chargeable to customer.
- 6. Any defect arising due to above consumables not changed as per scheduled or if used other than the recommended one.
- Never drive your bike through flooded roads or a flooded patch, as damages to the engine parts due to water entry is not covered under warranty.

Warranty : Scope & Limit



- 8. All chrome plated parts are prone to rust or corrosion in coastal area or in acidic environment or due to neglected cleaning etc. However chrome film peeling is covered under warranty in general at mospheric conditions. Blue/ Yellow colouration of silencer near exhaust port is permissible and hence not covered under warranty.
- Oxidation of unpainted/painted crankcase, cylinder block, cylinder head etc. in acidic environment or in a coastal area.
- 10.Parts of the vehicle that have been subjected to misuse, accident, negligent treatment OR which have been used in conjunction with parts & an equipment not manufactured or recommended for use by Bajaj Auto Limited, if found is the sole judgement of Bajaj Auto Limited, such use prematurely affects the performance and reliability of the vehicle.
- 11.Parts of the vehicle that have been altered and modified or replaced in unauthorized manner like use of wider tyres, loud silencers etc and which in the sole judgement of the Bajaj Auto Limited affects its performance and reliability.

- 12. Vehicles which are not being serviced at recommended dealers as per the service schedule described or which have not been operated or maintained in accordance with the instructions maintained in the Owner's Manual.
- 13.Vehicles used for any competition or race and/or for attempting to set up any kind of record.
- 14. Any failure arising due to use of adulterated or bad quality fuel.
 - Parts affected due to bad fuel quality are not covered $\mbox{\sf Under}$ warranty.
- 15.If additional electrical accessories such as Remote, Bigger horn, Musical brake light etc. fitted on vehicle.
- 16.If the vehicle has been used for commercial purpose like Taxi or any other means of commercial transportation.

Bajaj Auto Limited reserves the right to make any changes in design or to add any improvements on the vehicle at any time without incurring any obligation to install the same on a vehicle previously supplied and sold. Also, the conditions of this warranty are subject to alteration without any notice.

This warranty is the entire written warranty given by Bajaj Auto Limited for **Pulsar NS 125 BS VI"** motorcycle' and no other dealer or its or his agent or employee is authorised to extend or enlarge this warranty.

Delivery Certificate

Customer's Signature



FRAME NO.											
ENGINE NO.	: Sold on.:										
Customer's Name Mr/Mrs/Miss :											
Address	: Contact No.:										
I have taken possesi	I have taken possesion of motorcycle along with the following items.										
1. Owner's Manual	5. Standard Accessories										
2. 2 nos of key	6. Battery Make Sr. No										
3. Set of tools	7. Tyre Fr Make Sr. No										
4. First Aid Kit	Rr Make Sr. No										
	n delivered to my satisfaction & I have understood all terms and conditions of warranty, service schedules & d shall abide by them.										
	Dealer Code :										
	Dealer Name :										
	Address :										
Customer's Signat	(To be filled in by the dealer) Contact No. :										

(To be filled in by the dealer) Imp - Dealership should take customer sign & maintain the record of this 'Delivery Certificate'. MAKE OF BATTERY:



BATTERY WARRANTY CARD

MFG. CODE OF BATTERY:

BATTERY SR. NO.: SPECIAL SALE DATE: VEHICLE								_					
PAME OF OWNER AND ADDRESS: TYPE OF VEHICLE: REG. NO.: RAME NO.: ENGINE NO.: SERVICE RECORD Sr. Date Age Mths. Gravity Voltage Remarks Dealer's Stamp & Code Mths. Gravity Voltage Remarks Dealer's Stamp & Signature * Code For Remarks: LL : Low electrolyte level. AE : Electrical system needs attention. IR : Insufficient running of vehicle. CB : Cover broken. 4 BC : Broken Container.	BAT1	TERY SR	. NO.:					BA	TTERY (RY CHARGING DATE :			
PYPE OF VEHICLE:	YPE	OF BA	ΓΤΕRY :					. VE	HICLE S	SALE DATE :			
PYPE OF VEHICLE:	NAM	AME OF OWNER AND ADDRESS :											
PYPE OF VEHICLE: REG. NO.: RAME NO.: SERVICE RECORD Sr. Date Age Mths. Gravity Voltage Remarks Dealer's Stamp & Signature Parallel Signature P													
SCRIPTION ST. Date Age Mths. Gravity Voltage Remarks Dealer's Stamp & Signature *Code *Cod	YPE												
Sr. Date Age Mths. Gravity Voltage Remarks Dealer's Stamp & Signature *Code *Code For Remarks: LL: Low electrolyte level. AE: Electrical system needs attention. IR: Insufficient running of vehicle. CB: Cover broken. BC: Broken Container.	RAN	RAME NO.: ENGINE NO.:											
AE: Electrical system needs attention. IR: Insufficient running of vehicle. CB: Cover broken. BC: Broken Container.	ER\	ERVICE RECORD											
AE: Electrical system needs attention. IR: Insufficient running of vehicle. CB: Cover broken. BC: Broken Container.	Sr. No.	Date	Age Mths.	Specific Gravity	Voltage	Remarks	Dealer & Sig	's Stamp gnature	*Code				
3 CB : Cover broken. BC : Broken Container.										,			
BC : Broken Container.	2									IR : Insufficient running of vehicle.			
	3									CB : Cover broken.			
5 PM : Poor maintenance.	4									BC : Broken Container.			
*	5									PM : Poor maintenance.			
6 BA : Battery abused.	6									BA : Battery abused.			

Note: Customer should insist that "Service Record" must be filled by respective authorised battery dealer as proof of specified maintenance for easy settlement of claim, if any.

TO BE FILLED IN BY BATTERY DEALERS / DISTRIBUTORS IN CASE OF CLAIM



Name of Dealer & Code :								
Date of claim :Battery Type :								
Serial No. :		Date of Fitment :						
Failure Mode (Please tick as	applicable)							
 Loose connection 	 Overcharge / Und 	lercharge						
 Internal Short 	 Reverse Charge 							
Plate Shedding	 Does not Hold Ch 	arge						
 Wrong Assembly 	 Left Lying Idle 							
• Wrong Application	 Terminal Corroded 	1						
# Claim Accepted ##	# Claim Rejected							
Details of Repair, if any								
Note:								
Please contact nearest respe	ective authorised battery de	ealer for details immediately after purchase of vehicle.						

pulsar Notes

pulsar Notes

Use only Bajaj Genuine Parts







We are committed to provide the best of sales & service experience, however should you require any additional assistance, please call our Call centre on the number given below.

:7219821111

Call charges are as applicable

Call centre timings :- Monday to Sunday

(09:00 am - 08:00 pm)

*Please download customer care app from 'Google play store' and 'Apple store' and book the vehicles for servicing and more on your phone.

E-mail : customerservice@bajajauto.co.in

Web Site: www.bajajauto.com

CIN: L65993PN2007PLC130076